



ROCKWOOL Comfortbatt R-Value Expansion

Expand your R-value options with Comfortbatt R13, R21 and R38 Thermal Batt Insulation



Features and Benefits

- Comfortbatt is now available in a wider range of R-values, including R13, R21 and R38. Meet your minimum code requirements for exterior wall and attic applications
- Non-combustible and fire resistant, Comfortbatt® will not develop smoke or promote flame spread when exposed to fire
- Easy installation using a unique flexible edge design, simply insert, compress and release Comfortbatt into the stud space
- Higher density batts mean increased durability during product handling and installation
- Excellent noise reduction and sound absorption to help you create quieter, more productive environments
- Water and moisture resistant, Comfortbatt® will not promote mold growth
- Certified GreenGuard Gold, and holds Declare Red List Approved and BioPreferred Certification Labels

ROCKWOOL Comfortbatt Complete R-Value Range

R-value	Item Number	Dimensions	Pieces per Pack	Packs per Pal	SQ FT per Pack
13	294288	3.5" x 15.25" x 47"	12	12	59.7
13	294291	3.5" x 23" x 47"	8	12	60.1
15	169079	3.5" x 15.25" x 47"	12	12	59.7
15	169082	3.5" x 23" x 47"	8	12	60.1
21	294329	5.5" x 15.25" x 47"	8	12	39.8
21	294332	5.5" x 23" x 47"	5	12	37.5
23	169091	5.5" x 15.25" x 47"	8	12	39.8
23	169094	5.5" x 23" x 47"	5	12	37.5
30	169100	7.25" x 15.25" x 47"	6	12	29.9
30	169102	7.25" x 23" x 47"	4	12	30.0
38	294337	9.5" x 15.25" x 47"	4	12	19.9
38	294340	9.5" x 23" x 47"	3	12	22.5

For more information contact your local ROCKWOOL Sales Representative or visit www.rockwool.com/products/comfortbatt