



Stainless steel wall ties to suit structural requirements (By Others)

Masonry outer leaf (Typical 103mm brickwork) (By Others)

ROCKWOOL NyRock® Cavity Slab 032 (Thickness to suit required u-value)

Damp proof course (DPC) (Detail By Others)

Telescopic floor vent (By Others)

Internal lining and finishes (By Others)

Internal blockwork leaf to suit structural and thermal requirements (By Others)

FIREPRO Acoustic Intumescent Sealant

T&G chipboard flooring (By Others)

Vapour control layer

ROCKWOOL FLEXI (Thickness to suit required u-value)

Typical timber floor and foundation detail (By Others)

Continuous run of 25mm wire mesh stapled to sides of joists

Minimum 150mm clear void

Please refer to relevant ROCKWOOL product data sheet for further detail / specification / performance

This CAD Drawing is for illustration purposes only and shall not form part of any contract with ROCKWOOL or hold any contractual force.

Usage of the information remains under the sole responsibility of the purchaser and/or user

ROCKWOOL makes no warranty, representation or guarantee regarding the information contained in the CAD Drawing, the suitability of the products for any particular purposes or the continuing production of any product. To the maximum extent permitted by applicable law, ROCKWOOL disclaims (i) any and all liability arising out of the CAD drawing, the application, use of any product, misuse or inability to use the product (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all liability of any nature resulting from the use or reliance upon the information contained in this CAD Drawing. No express or implied warranties are given other than those implied by law.

Information contained in this CAD Drawing is up-to-date as at the date of issue. As ROCKWOOL Limited cannot control or anticipate the conditions under which the information contained in this CAD Drawing may be used, each user should review the information in specific context of the planned use and must obtain approval by Building Control and/or the overseeing body for the project, who are ultimately responsible for approving the correct application/specification.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of ROCKWOOL



Pencoed, Bridgend,  
South Wales CF35 6NY  
t: 01656 868490  
technical.solutions@rockwool.co.uk

Title: Ground Floor - Suspended Timber Floor Thermal ROCKFLOOR & NyRock® Cavity Slab 032

Scale: N.T.S.

Date: May 2022

Drawing Reference: RWSD-GEN-3103

Revision 1