

NBS Specification: FIREPRO® Glue

PRODUCT SUMMARY:

A fire resistant adhesive for use with ROCKWOOL Stone Wool systems.

PRODUCT GENERAL DESCRIPTION:

A water-based and fire-resistant adhesive with an approximate pH 11. It has been specially developed for fixing ROCKWOOL fire protection systems as well as other suitable ROCKWOOL products where a high-quality, fire-resistant adhesive is required.

FEATURES AND BENEFITS:

- This product has been authorised for use in LUL surface and sub-surface premises when installed in accordance with manufacturer's instructions.
- Cures in 4 hours (min) at approx. 20°C dry conditions
- Can be used from -10°C upward.

APPLICATION:

The product has been specially formulated for use with FIREPRO® BEAMCLAD/Fire Tube and ROCKWOOL Fire Duct Systems where glued joints or noggins are required.

FIREPRO® glue must always be stirred before use to ensure a uniform product consistency.

Generally, storage should be made in frost free conditions. Should frost exposure occur, the glue should be thawed out followed by thorough stirring. Frost exposure does not remove curing ability.

Firepro Glue is suitable for use where there is a requirement for a fire-resistant adhesive. The product has been widely used in fire tests conducted on ROCKWOOL Fire Protection Systems -achieving fire ratings of up to four hours

PRODUCT SPECIFICATION CLAUSE

PRODUCT REFERENCE:

FIREPRO Glue

PRODUCT PROPERTIES:

Available sizes: 17kg Tub, 300ml Cartridge

pH: 11

Resistance to fire rating: up to 4 hours (based on fire resistance test data for ROCKWOOL fire protection systems)

STANDARDS AND APPROVALS:

See specific product data sheets

CONTACT DETAILS:

ROCKWOOL

Wern Tarw Road, Rhiwceiliog Pencoed, Bridgend CF35 6NY

Email: technical.solutions@rockwool.co.uk

Telephone: 01656 868 490

www.rockwool.com/uk/