
NBS Specification: ROCKWOOL FIREPRO® SpeedSeal

PRODUCT SUMMARY:

A fast-sealing solution for small scale apertures.

PRODUCT GENERAL DESCRIPTION:

There are many instances in buildings where single or small bunched cables and conduits will need to be positioned through compartment walls. It is important that even the smallest penetrating service is effectively fire stopped to reinstate the fire performance of the wall. FIREPRO® SpeedSeal is a red putty-based penetration sealing solution available in 60 and 100 mm diameter discs. It has been tested in service openings 25 x 25 mm and 50 x 50 mm to seal penetrating services such as small metallic pipes, plastic pipes, cables and cable bunches.

Tested to reinstate the fire performance of rigid and flexible walls (minimum 100 mm) where small cables and conduits penetrate. Fire resistance testing to EN 1366-3 and proven to perform for up to EI 60.

FEATURES AND BENEFITS:

- Quick and easy to install.
- Up to E120 (integrity)/ EI60 (integrity and insulation) fire resistance.
- Two size options to suit the majority of small openings.
- Suitable for refurbishment or new build.

APPLICATION:

Used to seal penetrations through service openings. Tested in conjunction with small/ medium metallic pipes, plastic pipes, small/ medium cables and cable bunches. Can be used as a blank seal.

PRODUCT SPECIFICATION CLAUSE

PRODUCT REFERENCE:

Firepro SpeedSeal

PRODUCT PROPERTIES:

Fire resistance: [d] Up to 120 minutes fire resistance (E120)

Diameter:

- 60 mm
- 100 mm

Thickness: 4mm

Colour: Red

Density: [d] 1.55–1.6 g/cm³

STANDARDS & APPROVALS:

FIREPRO® SpeedSeal has been tested to BS EN 1366-3:2009

FIREPRO® SpeedSeal has been third party accredited through Certifire (CF 5850)

CONTACT DETAILS:

ROCKWOOL

Wern Tarw Road, Rhiwceiliog Pencoed, Bridgend CF35 6NY

Email: technical.solutions@rockwool.co.uk

Telephone: 01656 868 490

www.rockwool.com/uk/